# EAN Inkjet Printer

## Support 2 printheads  Cost-effective printer

- With HP TIJ 2.5 Technology
- With a 7 inch touch screen as controller, easy to edit print message
- User-Friendly Interface，Easy UI makes it accessible to operators of varying expertise levels
- support 1-2 print heads combined or separate freely
- Take HP original driving board to make print quality higher
- With RFID as encryption, more reliable for continuous sales
- Cost effective while support to print barcode and database
- Support multi-language editing and printing

hp Inkjet Technology Licensee
Shanghai Loogal

CE Certificate

FREE TRIAL

Compact and easy to install

High resolution Up to 600 dpi

Loogal test label
2023-06-02

| | |
|---|---|
| **Technology** | HP TIJ2.5 |
| **Operation system** | LINUX |
| **Controller** | 7 inch touch screen |
| **Print height** | EANJET-1　　　　　　　12.7mm<br>EANJET-2/EANJET-11　　25.4mm/12.7mm*2 |
| **Print speed** | 20m/min@600x300DPI<br>40m/min@300x300DPI<br>90m/min@150x300DPI |
| **Print frequency** | 1Ph, 17.5pcs/s@300x300DPI & 42m/min<br>2Ph, 10pcs/s@300x300DPI & 24m/min |
| **Resolution** | X:100/120/150/200/300/600　　　　　Y:300/600 |
| **Print content** | Text, date, counter, image, shift code, 1D&2D barcode, database, |
| **More functions** | Authority password/power saving mode/date format can be set flexibly/carry bit source counter can be set |
| **Barcode type** | 1D: EAN8\EAN13\EAN128\CODE25\CODE39\CODE128\Codebar2width\PIATS\PIATSDRUG\UPC12\CODE128A\CODE128B\CODE128C\UPC-E\ITF-14\ Code-2of5 Interleaved　2D:QRCODE\DATAMATRIX\PDF417 |
| **Communication** | NO |
| **Interface** | USB/Sensor/Encoder/Alarm |
| **Optional parts** | Encoder/Alarm/4 meters cable/Adjustable brackets |
| **Display language** | Chinese/Traditional Chinese/English/Spanish/Korean |
| **Printable language** | Chinese/Traditional Chinese/English/Spanish/Turkish/ |
| **Font supported** | Default: Arial/SourceHanSansSC Regular/SourceHanSerifCN-Regular<br>More: support .ttf format fonts which can be imported |
| **Upgrade** | Firmware and software both can be updated by USB |
| **Ink** | Support both water based and solvent based ink |
| **Power** | 60W /110-220VAC/ 50/60Hz |
| **Environment** | 5℃～35℃ / 10%～90% |
| **Weight/Dimension** | 3.5kg/37*35*14cm |